

HOT 1510 cod. 15364

Technical specifications

AR Code 15364

Max Pressure (bar) 150

Max Pressure (psi) 2175

Max flow (lph) 600

Max flow (gph) 159

Power (Kw) 3

RPM 1450

Power (Hz) 50

Power (V) 230

Unit size (mm) LxWxH 540x800x750

Packaging size 790x560x545

Net weight (Kg) 94

Pallet qty 4

20 feet container qty 44

40 feet container qty 100

Truck qty 132



INDUCTION



ROD-CRANK



BRASS



IPX5-S1



TSS®
Total Stop
SYSTEM

Product details

The professional pressure washer HOT 1510 is the AR Blue Clean hot water pressure washer, equipped with professional accessories, which allows you to remove the most stubborn and annoying dirt such as oil or grease. It is a professional model suitable for professionals who need to perform very frequent cleaning tasks that require maximum performance.

Inside, there is a pump with a brass head with 3 axial pistons driven by a high-performance connecting rod-crank system equipped with an automatic by-pass valve with pressure relief in the pump head and an induction motor with thermal protection.

The vertical stainless steel boiler with a double coil and refractory bottom, directly fed by the 8-liter diesel tank, allows, provided all conditions are met, to have an outgoing water temperature of up to 100°C. Additionally, it is equipped with a safety pressure switch that automatically shuts off the boiler in the absence of water. The control panel includes various indicators such as voltage, diesel, and flame. There is also a thermostat for regulating the water temperature.

Equipped with the TST – Total Stop System Timed – this machine activates in by-pass mode for a 20-second interval upon releasing the gun lever, ensuring a prompt restart within this period. This technology reduces wear on the pump-motor unit and limits energy consumption. After 20 seconds, the machine goes into Total Stop. This feature is particularly suitable in contexts where the pressure washer is subject to frequent interruptions and restarts.

The four rubber-tread wheels ensure easy maneuverability even on uneven terrain.

The professional accessories included in the package, to be connected to each other via a brass threaded connection, are: a high-pressure reinforced hose with a 10 m steel braid, a high-pressure gun with safety and metal core; lance with high/low pressure head in steel (56 cm) to be connected to the pressure washer gun via a threaded screw connection and finally a nozzle that must be mounted at the end of the lance allowing the water to exit at high pressure.

Standard accessories



Optional accessories

