

HOT 2315 cod. 24401-V

Technical specifications

AR Code	24401-V
Max Pressure (bar)	230
Max Pressure (psi)	3335
Max flow (lph)	900
Max flow (gph)	238
Power (Kw)	7.4
RPM	1450
Power (Hz)	3~50
Power (V)	400
Unit size (mm) LxWxH	980x590x920
Packaging size	1060x740x960
Net weight (Kg)	145
Pallet qty	2
20 feet container qty	22
40 feet container qty	50
Truck qty	66



INDUCTION



ROD-CRANK



BRASS



IPX5-S1



TSS®
Total Stop
SYSTEM

Product details

The 2315N hot water professional pressure washer from the Annovi Reverberi line is designed to offer high-level performance. Thanks to its ability to generate hot water, it is particularly effective in removing the most stubborn dirt, such as oil and grease, which resist traditional cleaning methods. Designed to meet the needs of professionals performing frequent and intensive cleaning tasks, it guarantees excellent results, also thanks to the professional accessories included, in sectors such as construction, livestock farming, crafts, car wash, and automotive.

It features a pump with a brass head, 3 axial ceramic pistons with a connecting rod-crank system, an automatic by-pass valve with pressure reset in the pump head, and a three-phase induction electric motor with thermal protection.

The vertical stainless steel boiler, with a burner cooling system operated by an independent electric motor, double coil, and refractory cement base, directly powered by a 15-liter diesel tank, allows, provided all conditions are met, to have an output water temperature of up to 110°C. Additionally, it is equipped with a safety pressure switch that automatically shuts down the boiler in case of water absence and a micro-leak detection board with an acoustic sensor. The control panel includes various indicators such as voltage, diesel, flame, and a thermostat for adjusting the water temperature.

Equipped with the TST – Total Stop System Timed – this machine activates in by-pass mode for a 20-second interval upon releasing the gun trigger, ensuring a prompt restart within that period. This technology reduces wear on the pump-motor assembly and limits energy consumption. After the 20 seconds, the machine switches to Total Stop. This feature is particularly suitable in contexts where the pressure washer is subject to frequent interruptions and restarts.

The four rubber-tread wheels ensure easy maneuverability even on uneven terrain. The professional accessories included in the package, to be connected via a brass threaded fitting, are: a 10 m reinforced high-pressure hose with steel braid, a high-pressure gun with safety lock and metal core; a lance with high/low pressure stainless steel nozzle (56 cm) to be connected to the pressure washer gun via threaded screw fitting, and finally a nozzle that must be mounted at the end of the lance allowing high-pressure water output.

Standard accessories



Trigger gun
cod. 3164090



3160590



**Lance with
fixed head
w/out nozzle**
cod 46221



3083

Optional accessories



40106



**Underbody
lance kit cod.**
40655



46496



43750



43747



**Pipe drain kit
16m cod.**
1272530



Pipe drain kit
cod. 1272520



**Walter filter
kit. cod. 43735**



**Water suction
kit. cod. 43724**



40840



3160620



Click fast kit.
cod. 40439



40652



40653



40654



40966



Steam nozzle.
cod. 50250



3251



40694



40695